



EB30HDRT-AM

Composite Codec emSFP™ Coaxial
Transceiver, MSA, HD-BNC™

Features

- SMPTE 259M-C compliant
- HD-BNC™ connectors (75Ω)
- Supported Composite Standards:
 - NTSC M, NTSC J, NTSC 4.43
 - PAL B/G/H/I/D, PAL M, PAL N, PAL 60
- Rx Channel:
 - 10-bit Composite to SD-SDI video decoder
 - 4x Oversampling (54Mhz)
 - Test Pattern Generation
- Tx Channel:
 - SD-SDI to Composite 10-bit video encoder
 - Up to 16x Oversampling (216Mhz)
 - Multiple Chroma & Luma filters
 - Test Pattern Generation
- Control via serial interface including:
 - Voltage & Temperature Monitoring
 - Module Information
 - Analog Status and Control registers
- Low Power Consumption - typical 1100mW
- Single Supply +3.3V
58.5mm x 13.4mm x 8.6mm SFP Package

Summary of Benefits

- **Flexibility:** Build a totally optimized system by mixing electrical SDI, NTSC/PAL converter and optical video SFP;
- **Cost:** Design cost effective system;
- **Modularity:** Allow hot scalability and replacement of critical components wherever possible;
- **Density:** Highest density ever achieved for standard 75Ω coaxial SDI interfaces combined with converters;
- **Time-to-market:** Reduce development cost and risk;
- **Interchangeable:** Fully compatible with existing MSA video optical SFP and SDI emSFP™;
- **Hot-Pluggable:** Swap without affecting system behaviour;
- **Advanced Packaging:** Support ganged cages, belly-to-belly and superposed cages mounting;
- **Inventory:** Just in time inventory management;
- **Green:** The EB30HDRT-AM is Pb-free and ROHS compliant.

Applications


- Low cost video converters replacement
- Processing cards
- Video routers
- Broadcast cameras

Overview

The EB30HDRT-AM is an electrical emSFP™ transceiver module designed to encode and decode composite signals over 75Ω coaxial cables via HD-BNC™ connectors. On the receive channel, the module decodes NTSC/PAL composite inputs and convert to SD-SDI signal. On the transmit channel, the module encodes the SD-SDI signal to NTSC/PAL composite.

The EB30HDRT-AM provides module identification information, configuration and diagnostic monitoring through a two wire serial interface. It is also a hot-pluggable solution for field system upgrade and maintenance.

The EB30HDRT-AM is interchangeable with other MSA optical video SFP or coaxial emSFP™ improving product flexibility. Ganged cages, belly-to-belly and superposed cages mounting are supported. The module is SMPTE compliant resulting in quick time-to-market and reduced development effort and cost. The EB30HDRT-AM is Pb-free and ROHS compliant.



Related Products

Part Number	Type (CVBS)	Pinout	Package	Temperature Range
EB30HDRT-AN	Rx/Tx	Non-MSA	SFP	0°C to 65°C
EB30HD2R-AN	2Rx	Non-MSA	SFP	0°C to 65°C
EB30HD2T-AN	2Tx	Non-MSA	SFP	0°C to 65°C
EB00CA02-xxA	HD-BNC to BNC cable adaptor			



sales@embrionix.com